

Universal Changeover switch



CA10 20A



CA10 32A



CA10 63A

CA10 Universal Changeover Switch

1. Specifications of CA10 Universal Changeover Switch:

Type		CA10-20	CA10-25	CA10-32	CA10-63	CA10-125	CA10-160
Rated Insulation Voltage Ui(V)		690	690	690	690	690	690
Conventional Heating Current Ith(A)Ac10		20	25	32	63	125	160
Rated Working Voltage Ue(V)		120 240 440	120 240 440	120 240 440	240 440	240 440	220 440
Rated Working Current Ie(A)	AC-21A	20 20	25 25	25 32 32	63 63	100 100	150 150
	AC-22A	20 20	25 25	25 32 32	63 63	100 100	150 150
	AC-23A	15 15	22 22	22 30 30	57 57	90 90	135 135
	AC-2	15 15	22 22	22 30 30	57 57	90 90	135 135

	AC-3	11 11	15 15	15 22 22	36 36	75 75	95 95
	AC-4	3.5 3.5	6.5 6.5	6.5 11 11	15 15	30 30	55 55
	AC-15	5 4	8 5	5 14 6			
	AC-13	5 1	9 1.5	25 11			
Rated Control Power (KW)	AC-23A	3.7/2.5 7.5/3.7	5.5/3 11/5.5	7.5/7 18/7.5	15/10 30/18.5	30/15 45/22	37/2275/37
	AC-2	4 7.5	5.5 11	7.5 15	18.5 30	30 45	37 55
	AC-3	3/2.2 5.5/3	1.5/1.1 3/2.2	3.7/1.5 5/5.3	5.5/2.4 7.5/4	6/3 12/5.5	10/4 15/7.5
	AC-4	0.55/0.75 1.5/1.5	1.5/1.1 3/2.2	3.7/1.5 5/5.3	5.5/2.4 7.5/4	6/3 12/5.5	10/4 15/7.5
Mechanical Life		60 10					
Electrical Life		AC-15 20 10 DC-13 6 10					

2. Dimension of CA10 Universal Changeover Switch:

